





The Premier-Slide provides power, safety and reliability encased in attractive an aluminium housing only 10cm high.

The Premier-Slide 100 provides the most comprehensive range of features that could be required in an automatic door operator. The robust construction and precise microprocessor technology make this sliding operator the premier choice for automatic sliding door solutions

The versatility of the Premier-Slide 100 integrates beautifully with today's modern building designs, linking effortlessly with access control, fire alarms and control systems.

Heavy duty steel brackets, reinforced toothed belt and a high quality extruded housing make this operator suitable for heavy and high usage door sets. Our use of nylon wheels on an aluminium track make for the quietest possible operation.

KEY FEATURES

- + Self Diagnostic for fault finding
 Faults appear on the screen with history of faults
- + Heavy duty Dunker Motor/ gearbox with internal electric lock
- + "Un-branded" We load your company logo onto the full colour screen
- + Easy Setup and simple wiring
- + Compact Only 10cm in height
- + Designed and manufactured in the UK.

DOOR FUNCTIONS

AUTOMATIC – Allows access from both directions

EXIT ONLY – Allows access from the internal activation only

ENTER ONLY – Allows access from the external activation only

CLOSED – All activations are ignored - The electric lock will engage

PHARMACY – Allows the door to open and lock at a specific point (5-20 % of the door open distance)

HOLD OPEN – The doors are held in the fully open position

PARTIAL OPEN – Opens to a percentage of the fully door width (sometimes called "winter mode")

AUTO WIDTH – Adjust between fully open and partially open depending on the frequency of traffic.









- 1 Flush-mounted switch
- 2 Surface-mounted switch
- 3 Dedicated canopy stay
- 4 Canopy-mounted switch

www.global-automatics.com
Tel: 0845 6430013